

### PRODUCT SPECIFICATIONS

## optical

Total HFOV 48° Exit Pupil (mm) 12 Eye Relief (mm) 26 Focus/convergence Collimated Monocular FOV (diagonal) 60° Vertical FOV 40° **Geometric Distortion** < 1% See-through Transmission 40%

### mechanical

**IPD Range (mm)** 55 to 73 **Weight (g)** 1300

# performance

Display TechnologyLCOS (reflective)Resolution1280x1024Contrast100:1Brightness (fL)30Spatial Resolution (arc-min/pixel)2.25

# **COMPATIBLE PRODUCTS**

# Video Control Units

- Advanced Video Control Unit
- Single Input / Dual Output SX Video Control Unit

### Audio Accessories

- Headphone Upgrade
- Headphone/Microphone Upgrade
- NVisor SX Integrated Microphone

# **Motion Trackers**

- InertiaCube 2+
- InertiaCube 3

### **Eve Trackers**

- Viewpoint Binocular Eyetracker
- Viewpoint Monocular Eyetracker

# Additional Accessories

• Reusable Shipping Case

# nVisor ST60 Head-Mounted Display

The nVisor ST60 is a professional see-through head-mounted display designed for augmented reality applications requiring a vivid, high-resolution display in a wide field-of-view format ideal for advanced training and simulation.

The nVisor ST60 is designed to provide users excellent clarity and visibility of their physical environment, while superimposing a bright virtual image across a 60° diagonal field-of-view. The low distortion optical design of the nVisor ST60 makes it ideal for professional simulation and industrial design applications requiring accurate registration between the virtual and physical environment. With light output of 30 fL, the ST60 is ideal for indoor environments with mixed lighting conditions.

The nVisor ST60 features external mounting points for most common headtrackers including the InertiaCube 2/3 from InterSense®, and the Flock-of-birds and 3D-Bird from Ascension Technology®. The nVisor ST60 has also been designed to accommodate unobtrusive internal mounting for the advanced six-degree-of-freedom IS-900 motion-tracker from InterSense.

Compatible with virtually any PC or workstation, the nVisor ST60 accepts VESA standard SXGA video in either digital or analog formats. The video control electronics support both stereoscopic and monoscopic viewing by detecting dual or single inputs automatically. An analog output is provided for driving a repeater monitor and a standard RS-232 port supports future firmware upgrades.

The nVisor ST60 is available on a worldwide basis directly from NVIS and through our reseller network.

