

HIGHEST PRECISON IN 3D METROLOGY

MEASURE THE ADVANTAGE



stereoSCAN

Especially in the context of demanding measuring tasks, the asymmetrical camera arrangement of the stereoSCAN provides optimum flexibility and reliability; even object areas which are difficult to access are captured fully and conclusively. The sturdy CFRP double structure of the sensor base allows for variable scanning positions - depending on your measuring task, the stereoSCAN even works standing on its head! Thanks to the system's exceptional sturdiness, it delivers high-precision, true-to-detail 3D data for further processing not only in the protected laboratory environment but also under the harsh and challenging conditions of an actual industrial production setting.

RANGE OF USE

Prime standard precision for innovative 3D projects:

- Inspection and quality control
- Process automation
- Digitization of design models
- CAD comparison to reference object
- Production optimization

- Automotive industry and suppliers
- Aviation and aerospace industries
- Electronics industry
- Casting industry
- Tooling and mold making industries
- Plastics industry



Application areas

- Inspection and measurement of free-form areas
- Faster prototyping processes
- Automated measurement processes
- Optimization of throughput times
- Surface area measurement with short takt times

HIGHEST PRECISION IN 3D METROLOGY

System configuration

- Wide selection of measuring fields for maximum feature accuracy
- High-resolution color or black-and-white cameras
- High-power LED in blue or white; optionally in green or red
- Measurement and evaluation software OPTOCAT
- Certified in accordance with VDI/VDE 2634
- Comprehensive range of accessories: Calibration plates,
- measurement tripod, robot, work stations, and many more





Contact-free, high-resolution 3D scanning for any type of object size, surface and material.



Three-dimensional metrology at the highest level accomplished by using a two-camera-system, which thanks to its excellent mechanical and thermal stability is universally usable: Whenever it comes to measuring the finest structures or minutest deviations, the stereoSCAN is the system of choice.

ADVANTAGES

- Sophisticated 3D metrology at the highest precision Automated measurement in
- Variable scanning positions thanks to CFRP double-base structure

- rough production environments
- Can be combined with a tactile probing sensor or a CMM
- High luminosity projector with LED in blue or white
- Seast and easily changeable measuring fields
- Three triangulation angles (10°, 20°, 30°)